



PRODUCTS

SP1000 SPREADER



The SP1000 is a simple-to-use, tandem-axle binder spreader trailer purpose-built for in situ stabilization. This trailer is cost-effective because it is accurate and has proven capable of consistent spread rates of plus or minus 10%

- Hopper capacity of 63.5 cubic feet
- Battery – 200amp AGM deep cycle battery
- Product spread width 5ft 2"
- Wireless remote for operator safety
- Tandem axle trailer with electric breaks and breakaway GVM -6,611lbs
- Tare weight – 3,086lbs
- Built in battery charger

PRODUCT SPECIFICATION - SP1000

Aggregate Trailer Mass (ATM)	6613lbs
Trailer Weight	3174lbs
Length	13ft 9.3"
Width	7ft 10.5"
Height	6ft 3"
Carry Capacity	63.5 ft³
Battery	200amp With Built in 25amp Battery Charger
Trailer Brake Type	Electric Brakes with Breakaway
Hopper Feed Type	Spreader Box Impeller
Axle	Dual Axel
Spread Width	5ft 3"
Drive System	Electric Over Hydraulic Drive

FEATURES & BENEFITS

- Designed by the industry for the industry
- The SP1000 has a hopper capacity of 63.5ft³
- Product spread width of 5ft 3"
- Accurate spread rate is governed by speed travelled
- Wireless remote control for operator safety.
- 200amp deep cycle battery with built in battery charger
- The SP1000 is light enough to be towed behind any utility/pickup that is fitted with electric trailer brake controls.
- Simple and safe to use
- Massive cost savings for heavy patching maintenance work



WWW.SHOULDERMASTERUS.COM